

HVP-40 DC High Voltage Probe To DMM

SPECIFICATIONS:

Model	HVP - 40
Ratio	1000 : 1 (1 KV = DMM 1 V Reading Value)
Input Impedance	1000M Ω \pm 7%
Temperature Coefficient	\leq 200 ppm / $^{\circ}$ C
Max. Input Voltage	DC: 0 ~ 40 KV AC: 0 ~ 28 KV (50 / 60 Hz)
Accuracy	DC: \pm 1% to 20 KV, \pm 2% to 40 KV AC: \pm 5% to 28 KV (50 / 60 Hz only)
Max. Loading Current	40 μ A at 40 KV DC
Max. Loading Power	1.6 Watt
Ground Load Length	90 cm (3 ft)
Output Cable Length	100 cm (3.3 ft)
Dimensions / Weight	340 mm x 80 \varnothing / About 230 g
Operating Temperature	0 $^{\circ}$ C ~ + 50 $^{\circ}$ C
Operating Temperature	-20 $^{\circ}$ C ~ + 70 $^{\circ}$ C

PINTEK

Pintek Electronics Co., Ltd

2F No.32 Tai-Pen Rd., Shulin Dist., New Taipei City, Taiwan

Tel: 886-2-86859562~3 ; 886-2-86861898

Fax: 886-2-86852081 ; 886-2-86861114

<http://www.pintek.com.tw>

E-Mail : pintek@pintek.com.tw ; pintek@ms26.hinet.net